

Aria Micro



Light fixture with high-performance LED light sources. Wall or ceiling installation. Composed by: frame, body, asymmetrical reflector, fixing springs or housing. Body in injection mould of aluminium. Frame in aluminium. Body and frame are painted with outdoor treatment three stages: nanotechnologies, antioxidant primer, polyester paint. Metalized polycarbonate reflector. Silicone gasket. Protection screen in tempered glass, 3mm-thick. Housing in bend metal. Electrical connection to the ballast by means of a cable with appropriate terminal board supplied with the fixture. White monochromatic LEDs available in 2 colour temperatures: Warm = 3000K Neutral = 4000K IP Rating IP65 or IP40. Insulation class III. Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions.


Black ● Silver ● White ○

LED IP65

IP65




Watt	Weight	Length	Luminous Flux (lm)	CCT	Color	Code
2,5W	0.60Kg	6 cm	57lm	3000K	●	NL31019VTK004
					●	NL31019VTK002
					○	NL31019VTK006





Watt	Weight	Length	Luminous Flux (lm)	CCT	Color	Code
2,5W	0.60Kg	6 cm	57lm	3000K	●	NL31018VTK004
					●	NL31018VTK002
					○	NL31018VTK006



Aria Micro LED	LED	luminaire
Power	2,5W	2,5W
Flux	165lm	57lm
CCT	3000K	3000K
CRI	=80(min.)	
Color Tolerance	MacAdam 4SDCM)	
Service Life	L70(10K)>60500h	
Efficiency		100%
Efficacy	72lm/W	21.11lm/W

Accessories

		Code
NO IMAGE AVAILABLE	Alimentatore 5,6W 350mA IP67	DV3001
NO IMAGE AVAILABLE	Alimentatore 11,2W 700mA IP67	DV3003
NO IMAGE AVAILABLE	Alimentatore 35W 350mA IP67	DV3004
NO IMAGE AVAILABLE	ALIMENT. 8,4W 350mA (indip.)	NL19032
NO IMAGE AVAILABLE	ALIMENT. 9,8W 700mA (indip.)	NL19035
NO IMAGE AVAILABLE	ALIMENT. 20W 700mA (indip.)	NL19036

NO
IMAGE
AVAILABLE